

*Ninja* 1000 ABS



**R RIDEOLOGY**

Forever embracing, "Commitment = IDEOLOGY" of "running = RIDE"  
That's what is Kawasaki's RIDEOLOGY.

REFINED SPORT-TOURER WITH ADVANCED ELECTRONICS  
OFFERS DREAM COMBINATION: NINJA + TOURING

**Kawasaki**

# Ninja 1000 ABS



Emerald Blazed Green/Metallic Graphite Grey



Metallic spark black/Metallic graphite gray

## Sharp Ninja styling

All-new bodywork includes a much sharper front cowl with a decidedly closer resemblance to Kawasaki's Ninja supersport models. The more aggressive visage is complemented by fierce new LED headlamps. The dynamic and sporty bodywork reflects the Ninja 1000's exciting street riding potential.

## Exhilarating Engine

Engine tuning focused on the feeling the rider gets when opening the throttle. Strong torque is complemented by direct throttle response. Revised engine settings offer even smoother power delivery and cleaner emissions.

## Aluminium Twin-tube Frame

The highly rigid aluminium frame features a high degree of mass centralisation, ensuring a balance of sharp turning and firm handling.

- The vehicle weight includes fuel, lubricating oil, cooling water, and battery liquid.
- The manufacture may make improvements to specifications without prior notice.
- The catalogue photographs may have different specifications from the actual ones.
- The actual color may be different from the ones shown due to factors such as printing and photography.

## SPECIFICATIONS

Engine type	Liquid-cooled, 4-stroke In-Line Four
Displacement	1,043 cc
Compression ratio	11.8:1
Bore and Stroke	77.0 x 56.0 mm
Valve system	DOHC, 16 valves
Fuel system	Fuel injection: ø38 mm x 4 with oval sub-throttles
Ignition	Digital
Starting	Electric
Lubrication	Forced lubrication, wet sump
Maximum power	104.5 kW {142 PS} / 10,000 rpm
Maximum torque	111.0 N.m {11.3 kgf.m} / 7,300 rpm
Frame Type	Twin-tube, aluminium
Caster / Trail	24.5° / 102 mm
Overall length	2,100 mm
Overall width	790 mm
Overall height	1,185 mm
Seat height	815 mm
Wheelbase	1,440 mm
Ground clearance	130 mm
Curb mass	235 kg
Fuel capacity	19 litres
Suspension format (Front)	ø41 mm inverted fork with compression and rebound damping and spring preload adjustability
(Rear)	Horizontal Back-link, gas-charged rear shock with rebound damping and spring preload adjustability
Wheel travel (Front)	120 mm
(Rear)	144 mm
Tyre size (Front)	120/70ZR17M/C (58W)
(Rear)	190/50ZR17M/C (73W)
Brake type (Front)	Dual semi-floating ø300 mm petal discs
Caliper	Dual radial-mount, monobloc, opposed 4-piston
(Rear)	Single ø250 mm petal disc
Caliper	Single-piston
Steering angle (left/ right)	31° / 31°
Color	Emerald Blazed Green/Metallic Graphite Grey Metallic spark black/Metallic graphite gray

Kawasaki

We give you an optimal bike life

Please get in touch with us for any queries or questions regarding purchase of Kawasaki vehicles.

### India Kawasaki Motors Pvt.Ltd.

Building B, Multi-Modal Logistics and Industrial Park P-5, Phase-II, Chakan Industrial Area, Village Khalumbare, Tal-Khed, District Pune - 410501



<http://www.kawasaki-india.com/>